

Section 1 - Identification of The Material and Supplier

Spirit Marble & Tile Care Pty Ltd
1/36 Seton Rd
Moorebank, NSW 2170

Phone: 02 9734 6937 (business hours only)
Fax: 02 9601 7292

Chemical nature: Blend of ingredients in isopropyl alcohol.
Trade Name: **Spirit Hard Surface Seal**
Product Use: Stone & tile sealant.
Creation Date: **July, 2012**
This version issued: **August, 2016** and is valid for 5 years from this date.
Poisons Information Centre: Phone 13 1126 from anywhere in Australia

Section 2 - Hazards Identification**Statement of Hazardous Nature**

This product is classified as: Xn, Harmful. Xi, Irritating. F+, Highly Flammable. Hazardous according to the criteria of SWA.

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

SUSMP Classification: None allocated.

ADG Classification: Class 3: Flammable liquids.

UN Number: 1219, ISOPROPANOL (ISOPROPYL ALCOHOL)

**GHS Signal word: DANGER**

Flammable liquids Category 2

Serious eye damage/eye irritation Category 2B

Specific Target Organ Toxicity - Single Exposure Category 3

HAZARD STATEMENT:

H225: Highly flammable liquid and vapour.

AUH066: Repeated exposure may cause skin dryness or cracking

H320: Causes eye irritation.

H336: May cause drowsiness or dizziness.

PREVENTION

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P233: Keep container tightly closed.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing mist, vapours and spray.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well ventilated area.

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P301 + P312: IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.

P303 + P361 + P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin or hair with water until product is removed.

P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370 + P378: In case of fire: Use carbon dioxide, dry chemical, foam or water fog for extinction.

STORAGE

P405: Store locked up.

P403 + P235: Store in a well-ventilated place. Keep cool.

DISPOSAL

P501: Dispose of contents and containers to incineration if possible.

SAFETY DATA SHEET

Emergency Overview

Physical Description & Colour: Clear, colourless liquid.

Odour: Characteristic alcohol odour.

Major Health Hazards: No major health hazards. Eye irritant, repeated exposure may cause skin dryness or cracking, vapours may cause drowsiness and dizziness.

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc,%	TWA (mg/m ³)	STEL (mg/m ³)
Isopropanol	67-63-0	>80	983	1230
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

Skin Contact: Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 10 minutes or until chemical is removed. If irritation persists, repeat flushing and obtain medical advice.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 20 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Try to contain spills, minimise spillage entering drains or water courses.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

Flash point: 12°C

Upper Flammability Limit: 12.7%

Lower Flammability Limit: 2.0%

Autoignition temperature: 299°C

Flammability Class: Flammable Category 2 (GHS); Highly Flammable (AS1940).

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include Viton, Nitrile, butyl rubber, PE/EVAL, Responder. Eye/face protective equipment should comprise as

SAFETY DATA SHEET

a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. It should be fitted with a type A cartridge, suitable for organic vapours. Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Avoid using sawdust or other combustible material. Any electrical equipment should be non-sparking. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Can be slippery on floors, especially when wet. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 2500kg or L of Dangerous Goods of Packaging Group II, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: **AS/NZS 4501 set 2008**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

ASCC Exposure Limits	TWA (mg/m ³)	STEL (mg/m ³)
Isopropanol	983	1230

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

Skin Protection: You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: Viton, nitrile, butyl rubber, PE/EVAL, Responder.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Eyebaths or eyewash stations and safety deluge showers should be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Clear, colourless liquid.
Odour:	Characteristic alcohol odour.
Boiling Point:	82°C at 100kPa
Freezing/Melting Point:	No specific data. Liquid at normal temperatures.
Volatiles:	>95%
Vapour Pressure:	6kPa at 25°C
Vapour Density:	No data.
Specific Gravity:	0.8 approx

SAFETY DATA SHEET

Water Solubility:	Soluble.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water Distribution:	No data
Autoignition temp:	299°C

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

Incompatibilities: oxidising agents.

Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form hydrogen fluoride gas and other compounds of fluorine. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Toxicity: IMMEDIATE (ACUTE) EFFECTS:

Oral LD₅₀ (rat): 5045 mg/kg

Inhalation LC₅₀ (rat): 16,000 ppm/8 hours

Skin LD₅₀ (rabbit): 12,800 mg/kg

Skin Irritation (rabbit): 500 mg - mild

Eye Irritation (rabbit): 10 mg - moderate: 100 mg - severe

DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS:

Subchronic Inhalation (rat): TCLo 5000 ppm/6 hr/day for 90 days (intermittent) caused a change in motor activity.

Chronic Inhalation (rat): TCLo 2500 ppm/6 hr/day for 2 years (intermittent) caused changes in liver and bladder weight and changes in urine composition.

OTHER DATA: Some very rare cases of skin hypersensitivity to Isopropanol have been reported. However, these cases do not at this time warrant Isopropanol to be classed as a sensitiser. There is no data to hand indicating any particular target organs.

Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Isopropanol	Conc>=20%: Xi; R36

Potential Health Effects

Inhalation:

Short Term Exposure: High vapour pressures may cause drowsiness and dizziness. In addition product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: Vapours may cause drowsiness and dizziness.

Skin Contact:

Short Term Exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However product is believed to be mildly irritating, but is unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: Repeated exposure may cause skin dryness or cracking.

Eye Contact:

Short Term Exposure: This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

Long Term Exposure: No data for health effects associated with long term eye exposure.

SAFETY DATA SHEET

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: Isopropanol is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

Section 12 - Ecological Information

This product is biodegradable. It will not accumulate in the soil or water or cause long term problems. Expected to not be an environmental hazard.

Biodegradation: 58% theoretical BOD, 5 days at 20°C - Relatively biodegradable.

Bioconcentration: Not expected to bioaccumulate in aquatic organisms based on low octanol/water partition coefficient.

Acute Toxicity (fathead minnow): LC₅₀ 10.4 g/L /96 hr.

Section 13 - Disposal Considerations

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable, consider controlled incineration, or landfill.

Section 14 - Transport Information

UN Number: 1219, ISOPROPANOL (ISOPROPYL ALCOHOL)

Hazchem Code: •2YE

Special Provisions: None allocated

Limited quantities: ADG 7 specifies a Limited Quantity value of 1 L for this class of product.

Dangerous Goods Class: Class 3: Flammable liquids.

Packing Group: II

Packing Instruction: P001, IBC02

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition)
AICS	Australian Inventory of Chemical Substances
SWA	Safe Work Australia, formerly ASCC and NOHSC
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons

SAFETY DATA SHEET

UN Number

United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (February 2016)
Copyright © Kilford & Kilford Pty Ltd, August, 2016.

<http://www.kilford.com.au/> Phone (02)9251 4532

SAFETY DATA SHEET