

NATURAL PAVING SEAL

Technical Data Sheet

Product Description

A solvent based penetrating (impregnating) sealer that provides a natural look finish with long life benefits. **Spirit Natural Paving Seal** provides excellent protection from oil & waterborne staining.

Water-based	Penetrating (impregnating) Sealer	Can be used in wet areas (showers & water features)	Can be used on polished surfaces	Can be used internally or externally
NO	YES	YES	YES	BOTH
Allows Moisture Vapour Transmission	Repels Oil & Water	Alters appearance	Alter slip resistance	Can be used prior to grouting
YES	YES	NO	NO	YES*

*We recommend using **Spirit Pre Seal** for sealing prior to grouting, unless on Bluestone.

Where to Use

Internal & external porous tile, stone & concrete surfaces.

- Natural stones such as Travertine, Limestone, Marble, Bluestone, Sandstone, Granite, Quartz
- Terracotta
- Concrete & Clay Pavers
- Porcelain Tiles

Expected Wear

Weather conditions, harsh cleaning methods using high-alkaline, acid or solvent-based cleaners will affect the long term performance of the sealer. Following the appropriate **Spirit Guide** relating to your substrate will ensure the very best protection.

Coverage

Coverage will depend on porosity of the substrate, temperature and method of application. Approximate coverage allows for **2 coats** and is as follows:

- Concrete Pavers – 6-8 square metres per litre
- Sandstone, Limestone – 6-8 square metres per litre
- Terracotta, Clay Pavers, Slate – 8-10 square metres per litre
- Marble, Travertine, Granite – 10-12 square metres per litre
- Porcelain Tiles, Tessellated Tiles, Polished Stone/Porcelain 15-20 square metres per litre

Available Sizes

1lt, 4lt, 10lt & 20lt Drum.