



## **SPIRIT SAFE STRIPPER**

### **Technical Data Sheet**

#### **Product Description**

A very effective safe to use acrylic floor stripper for the removal of surface/topical sealers like **Spirit Uni Seal**. It is water soluble with no offensive odours.

#### **Features + Benefits**

- Safe to use, does not contain acids, non-flammable, no fumes
- Excellent for removing paint & glues
- Strips **Spirit Uni Seal**
- Most effective when used in conjunction with **Spirit H.D.C**

#### **Where to use:**

- All natural stone surfaces
- Ceramic tiles & porcelain tiles
- Concrete & Clay pavers

#### **Available sizes**

1lt, 4lt, 15lt

**CLEANER & SEALERS FOR THE TILING INDUSTRY**



## STRIPPING WITH SAFE STRIPPER

**Before commencing stripping, it is a requirement to test first before use.**

### Surface preparation

1. Sweep or vacuum the area to be stripped to remove any loose debris.
2. Protect carpet and household items if using indoors. If possible, remove or protect outdoor furniture to prevent contact with the stripper.



### Testing instructions

Test a spot first in an inconspicuous area to ensure competence and satisfaction. Only do a very small area at this stage. Follow the how to use guide below.

**Note:** The testing phase is extremely important as it allows you to determine if you are satisfied with the results, while also allowing you to familiarize yourself with how the product works.

### How to use

1. Apply **Spirit Safe Stripper** neat directly to the area to be stripped and allow it to dwell for 15-30 minutes for the stripper to take effect. The time may be weather dependent.
  2. Test by rubbing a gloved finger over the area to see if **Spirit Safe Stripper** has softened the existing sealer. It should feel like a gummy texture. Do not scrub yet.
  3. Now mix up some **Spirit HDC** in a clean bucket with warm water at a dilution rate of 1 part **Spirit HDC** to 8 parts clean warm water and scrub thoroughly with a nylon scouring pad.
  4. Remove the slurry with a broom and rinse with clean water. The water doesn't need to be cold for rinsing.
  5. Allow the floor to dry to see if there is still any sealer remaining. If there is still sealer remaining, follow the above process again.
- Note:** If a floor has been repeatedly sealed over the years without stripping it may take more than 2 goes to get the job done.
6. After total removal of the sealer/coating, rinse the floor thoroughly at least twice with **Spirit Neutral Cleaner** to help neutralise any residual stripper.
  7. Allow the floor to dry completely before applying any of Spirit's sealers

### Precautions

1. **DO NOT** mix **Spirit Safe Stripper** with any other cleaners other than specified, as harmful fumes may result.
2. All surrounding areas that are not intended to be stripped must be protected from contact with **Spirit Safe Stripper** to avoid inadvertent damage.
3. Appropriate gloves, goggles and long-sleeved shirt must be worn during application.
4. Wash hands with soap and water after use to remove any residue that may be on the skin.
5. In the event of an unwanted spill, wipe up immediately with a clean cloth and rinse with water
6. Regardless of the surface to be stripped, conduct a test first.

**Coverage** Depends on the porosity of the surface, temperature and method of application. 1 litre of **Spirit Safe Stripper** is capable of stripping approximately 10-20m<sup>2</sup>. Clean up tools after application with water.